

2002 TOW RATINGS

Compiled by Chris Hemer

For 2002 there are even more new models, not to mention a multitude of new technologies sure to find favor with RVers. To help simplify things, we have combined some columns, such as conventional/fifth-wheel tow ratings and manual/automatic tow ratings. This not only helps shorten the guide, it makes it easier for you to make direct comparisons between truck/trailer setups with respect to their maximum tow capacities. In addition, you'll note that we have excluded passenger car tow ratings from this year's list (since precious few are rated to tow more than 2,000 pounds), as well as some less-popular vehicle models. These vehicles will be included in the complete TL tow rating booklet, available separately. And as usual, vehicles capable of towing under 2,000 pounds will be excluded from both guides.

Every effort has been made to ensure the accuracy of all ratings, but because our information is often preliminary at the time of publication, some numbers may have changed by the time you visit your dealer's showroom. When in doubt, consult the manufacturer's towing guide (available at your dealership) or the vehicle owner's manual to be certain.

ACURA

Vehicle	Engine	Tow Limit (lbs)
Acura RL	3.5 V-6	2,000
Acura MDX	3.5 V-6	4,500a,b

a=requires automatic transmission and power steering coolers when towing more than 2,000 lbs; b=maximum rated capacity of 4500 lbs is for towing boats, 3,500 for towing other trailers.

BMW

Vehicle	Engine	Tow Limit (lbs)
BMW X5 4.6is	4.6 V8	6,000 a,b,d
BMW X5	4.4 V8	6,000a,b,d
BMW X5	3.0 I-6	6,000a,b,c
BMW X5	3.0 I-6	5,000a,b,d

a=Maximum towing weight for trailers without brakes is 1,650 lbs; b=Maximum towing weight for trailers with brakes off-road, 3,300 lbs; c=With manual transmission; d=With automatic transmission

BUICK

Vehicle	Engine	Tow Limit
Rendezvous	3.4 V-6	3,500a

a=requires towing package.

CADILLAC

Vehicle	Engine	Tow Limit (lbs)
Escalade AWD	6.0 V-8	8,200
Escalade 2WD	5.3 V-8	7,400
Escalade EXT	6.0 V-8	7,900

a=Requires trailer-towing package.

CHEVROLET/GMC

Astro/Safari and Venture Minivans

Vehicle	Engine	Tow Limit (lbs)
RWD CV	4.3 V-6	5,300a
RWD CV	4.3 V-6	5,800b
RWD PV	4.3 V-6	4,900a
RWD PV	4.3 V-6	5,400b
AWD CV	4.3 V-6	5,100a
AWD CV	4.3 V-6	5,600b
AWD PV	4.3 V-6	4,700a
AWD PV	4.3 V-6	5,200b
Venture	3.4 V-6	3,500d

Express/Savana

Vehicle	Engine	Tow Limit (lbs)
G1500 CV	4.3 V-6	4,700a
G1500 CV	4.3 V-6	5,200b
G1500 CV	5.0 V-8	5,600a
G1500 CV	5.7 V-8	6,100a
G1500 PV	4.3 V-6	4,200a
G1500 PV	4.3 V-6	4,700b
G1500 PV	5.0 V-8	5,100a
G1500 PV	5.7 V-8	5,600a
G1500 PV	5.7 V-8	6,600b
G2500 CV	4.3 V-6	4,500a
G2500 CV	5.0 V-8	5,400a
G2500 CV	5.7 V-8	5,900a
G2500 CV HD	4.3 V-6	5,200c
G2500 CV HD	5.7 V-8	6,600b

Vehicle	Engine	Tow Limit (lbs)
G2500 CV HD	5.7 V-8	8,100c
G2500 CV HD	6.5 TD	8,600b/c
G2500 LWB CV	4.3 V-6	4,300a
G2500 LWB CV	5.0 V-8	5,200a
G2500 LWB CV	5.7 V-8	5,700a
G2500 LWB CV HD	4.3 V-6	5,000c
G2500 LWB CV HD	5.7 V-8	6,400b
G2500 LWB CV HD	5.7 V-8	7,900c
G2500 LWB CV HD	6.5 TD	8,400b/c
G2500 PV	5.7 V-8	6,000b
G2500 PV	5.7 V-8	7,500c
G2500 PV	6.5 TD	8,000b/c
G2500 LWB PV	5.7 V-8	5,800b
G2500 LWB PV	5.7 V-8	7,300c
G3500 CV	5.7 V-8	6,400b
G3500 CV	5.7 V-8	7,900c
G3500 CV	8.1 V-8	9,100b
G3500 CV	8.1 V-8	10,000c
G3500 CV	6.5 TD	8,600b/c
G3500 LWB CV	5.7 V-8	6,200b
G3500 LWB CV	5.7 V-8	7,700c
G3500 LWB CV	8.1 V-8	8,900b
G3500 LWB CV	8.1 V-8	10,000c
G3500 LWB CV	6.5 TD	8,400b/c
G3500 PV	5.7 V-8	5,800b
G3500 PV	5.7 V-8	7,300c
G3500 PV	8.1 V-8	8,500b
G3500 PV	8.1 V-8	10,000c
G3500 PV	6.5 TD	8,000b/c
G3500 LWB PV	5.7 V-8	5,600b
G3500 LWB PV	5.7 V-8	7,100c
G3500 LWB PV	8.1 V-8	8,300b
G3500 LWB PV	8.1 V-8	10,000c
G3500 LWB PV	6.5 TD	7,800b/c

LWB=Long Wheelbase; PV=Passenger Van; CV=Cargo Van; TD=Turbo Diesel; a=3.42:1 axle ratio; b=3.73:1 axle ratio; c=4:10:1 axle ratio; d= requires heavy duty tow package.

Blazer

Vehicle	Engine	Tow Limit (lbs)
2dr. 2WD	4.3 V-6	4,700a,c
2dr. 2WD	4.3 V-6	5,700a,d
2dr. 2WD	4.3 V-6	4,200b,d
Blazer Xtreme 2dr. 2WD	4.3 V-6	2,000a,b,d
4dr. 2WD	4.3 V-6	4,500a,c
4dr. 2WD	4.3 V-6	5,500a,d
2dr. 4WD	4.3 V-6	4,400a,c
2dr. 4WD	4.3 V-6	5,400a,d/e
2dr. 4WD	4.3 V-6	3,900b,d
Blazer ZR2	4.3 V-6	4,100b,e
Blazer ZR2	4.3 V-6	4,600a,e
4dr. 4WD	4.3 V-6	4,200a,c
4dr. 4WD	4.3 V-6	5,200a,d/e
4dr. 4WD	4.3 V-6	3,600b,d

S-10/Sonoma

Vehicle	Engine	Tow Limit (lbs)
Regular Cab	2.2 I-4	3,200a,f
Regular Cab	4.3 V-6	4,000a,c
Regular Cab	4.3 V-6	5,000a,c

Vehicle	Engine	Tow Limit (lbs)
Regular Cab	4.3 V-6	6,000a,d
Extended Cab	2.2 I-4	2,000b,f
Extended Cab	2.2 I-4	3,000a,f
Extended Cab	4.3 V-6	3,800b,c
Extended Cab	4.3 V-6	4,800a,c
Extended Cab	4.3 V-6	5,800a,d
Long Bed*	2.2 I-4	2,200b,f
Long Bed*	2.2 I-4	3,100a,f
Long Bed*	4.3 V-6	3,900b,c
Long Bed*	4.3 V-6	4,900a,c
Long Bed*	4.3 V-6	5,900a,d
Extended cab 4WD	4.3 V-6	4,000b,d
Extended cab 4WD	4.3 V-6	5,500a,d/e
S-10 ZR2	4.3 V-6	4,200b,e
S-10 ZR2	4.3 V-6	4,700a,e
Crew Cab 4WD	4.3 V-6	5,200a,d/e

a=automatic transmission; b=manual transmission; c=3.08:1 rear axle ratio; d=3.42:1 rear axle ratio; e=3.73:1 rear axle ratio; f=4.10:1 rear axle ratio; *late availability

Chevy Avalanche 1500/2500

Vehicle	Engine	Tow Limit (lbs)
1500 CC	5.3 V-8	7,300d
1500 CC	5.3 V-8	8,300e
2500 CC	8.1 V-8	10,400d
2500 CC	8.1 V-8	12,000e
1500 CC 4WD	5.3 V-8	7,100d
1500 CC 4WD	5.3 V-8	8,100e
2500 CC 4WD	8.1 V-8	10,100d
2500 CC 4WD	8.1 V-8	12,000e

Sierra/Silverado Light Duty, Automatic Transmission, Conventional/Fifth-Wheel Towing (Automatic or Manual with 6.0 V-8)

Vehicle	Engine	Tow Limit (lbs) Conv/5th-Wheel
1500	4.3 V-6	4,600a/NA
1500	4.3 V-6	5,200c/NA
1500	4.8 V-8	6,600c/6,500c
1500	4.8 V-8	7,600d
1500	5.3 V-8	7,600c
1500	5.3 V-8	8,600d
1500 EC	4.3 V-6	4,700c/NA
1500 EC	4.3 V-6	5,200d/NA
1500 EC	4.8 V-8	6,100c
1500 EC	4.8 V-8	7,300d
1500 EC	5.3 V-8	7,300c
1500 EC	5.3 V-8	8,300d
CC	6.0 V-8	8,300d
CC	6.0 V-8	10,300e
1500 LB	4.3 V-6	4,500a/NA
1500 LB	4.3 V-6	5,100c/NA
1500 LB	4.8 V-8	6,500c/6,400c
1500 LB	4.8 V-8	7,500d
1500 LB	5.3 V-8	7,500c
1500 LB	5.3 V-8	8,500d
1500 LB EC	4.8 V-8	6,100c
1500 LB EC	4.8 V-8	7,100d
1500 LB EC	5.3 V-8	7,100c
1500 LB EC	5.3 V-8	8,100d

Vehicle	Engine	Tow Limit (lbs) Conv/5th-Wheel
2500 LB	6.0 V-8	8,800d
2500 LB	6.0 V-8	10,800e
Sierra Denali	6.0 V-8	10,000
1500 4WD	4.3 V-6	4,800c/NA
1500 4WD	4.3 V-6	5,400d/NA
1500 4WD	4.8 V-8	7,300d/7,200d
1500 4WD	4.8 V-8	8,300e/8,200e
1500 4WD	5.3 V-8	8,300d
1500 4WD	5.3 V-8	9,300e
1500 4WD EC	4.8 V-8	6,800d
1500 4WD EC	4.8 V-8	8000e
1500 4WD EC	5.3 V-8	8,000d
1500 4WD EC	5.3 V-8	9,000e
1500 4WD CC	6.0 V-8	8,000d
1500 4WD CC	6.0 V-8	10,000e
1500 4WD LB	4.3 V-6	4,700c/NA
1500 4WD LB	4.3 V-6	5,200d/NA
1500 4WD LB	4.8 V-8	7,100d
1500 4WD LB	4.8 V-8	8,100e
1500 4WD LB	5.3 V-8	8,100d
1500 4WD LB	5.3 V-8	9,100e
1500 4WD LB EC	4.8 V-8	6,700d
1500 4WD LB EC	4.8 V-8	7,700e
1500 4WD LB EC	5.3 V-8	7,700d
1500 4WD LB EC	5.3 V-8	8,700e
2500 4WD EC	6.0 V-8	8,300d
2500 4WD EC	6.0 V-8	10,300e

Sierra/Silverado Light Duty, Manual Transmission, Conventional Towing

Vehicle	Engine	Tow Limit (lbs)
1500	4.3 V-6	3,600a
1500	4.3 V-6	4,200c
1500	4.8 V-8	4,600c
1500	4.8 V-8	5,600d
1500 EC	4.3 V-6	3,700c
1500 EC	4.8 V-8	4,200c
1500 EC	4.8 V-8	5,300d
1500 LB	4.3 V-6	3,600a
1500 LB	4.3 V-6	4,100c
1500 LB	4.8 V-8	4,500c
1500 LB	4.8 V-8	5,500d
1500 LB EC	4.8 V-8	4,100c
1500 LB EC	4.8 V-8	5,100d
2500 LB	6.0 V-8	8,800d
2500 LB	6.0 V-8	10,800e
1500 4WD	4.3 V-6	3,800c
1500 4WD	4.3 V-6	4,400d
1500 4WD	4.8 V-8	5,300d
1500 4WD	4.8 V-8	6,300e
1500 4WD EC	4.8 V-8	5,000d
1500 4WD EC	4.8 V-8	6,000e
1500 4WD LB	4.3 V-6	3,800c
1500 4WD LB	4.3 V-6	4,300d
1500 4WD LB	4.8 V-8	5,200d
1500 4WD LB	4.8 V-8	6,200e
1500 4WD LB EC	4.8 V-8	4,800d
1500 4WD LB EC	4.8 V-8	5,800e
2500 4WD EC	6.0 V-8	8,300d
2500 4WD EC	6.0 V-8	10,300e

Sierra/Silverado Heavy Duty, Automatic or Manual Transmission, Conventional/Fifth-Wheel Towing

Vehicle	Engine	Tow Limit (lbs) Conv/5th-Wheel
2500 EC	6.0 V8	10,300e
2500 EC	8.1 V8	12,000d-e/13,900d; 15,900e
2500 EC	6.6 TD	12,000d/15,800d
2500 CC	6.0 V8	10,100e
2500 CC	8.1 V8	12,000d-e/13,700d; 15,700e
2500 CC	6.6 TD	12,000d/15,600d
2500 LB	6.0 V8	10,500e
2500 LB	8.1 V8	12,000d-e/14,300d; 16,300e
2500 LB	6.6 TD	12,000d/16,200d
2500 LB EC	6.0 V8	10,200e
2500 LB EC	8.1 V8	12,000d-e/13,800d; 15,800e
2500 LB EC	6.6 TD	12,000d/15,700d
2500 LB CC	6.0 V8	10,000e
2500 LB CC	8.1 V8	12,000d-e/13,500d; 15,500e
2500 LB CC	6.6 TD	12,000d/15,400d
3500 LB	6.0 V8	10,200e
3500 LB	8.1 V8	12,000e/15,800e
3500 LB	6.6 TD	12,000d/15,600d
3500 LB EC	6.0 V8	9,800e
3500 LB EC	8.1 V8	12,000e/15,400e
3500 LB EC	6.6 TD	12,000d/15,300d
3500 LB CC	6.0 V8	9,600e
3500 LB CC	8.1 V8	12,000e/15,300e
3500 LB CC	6.6 TD	12,000d/15,100d
2500 4WD EC	6.0 V8	10,200e
2500 4WD EC	8.1 V8	12,000d-e/13,600d; 15,600e
2500 4WD EC	6.6 TD	12,000d/15,500d
2500 4WD CC	6.0 V8	9,800e
2500 4WD CC	8.1 V8	12,000d-e/13,400d; 15,400e
2500 4WD CC	6.6 TD	12,000d/15,300d
2500 4WD LB	6.0 V8	10,200e
2500 4WD LB	8.1 V8	12,000d-e/13,800d; 15,800e
2500 4WD LB	6.6 TD	12,000d/15,700d
2500 4WD LB EC	6.0 V8	9,900e
2500 4WD LB EC	8.1 V8	12,000d-e/13,800d; 15,800e
2500 4WD LB EC	6.6 TD	12,000d/15,500d
2500 4WD LB CC	6.0 V8	9,700e
2500 4WD LB CC	8.1 V8	12,000d-e/13,200d; 15,200e
2500 4WD LB CC	6.6 TD	12,000d/15,100d
3500 4WD LB	6.0 V8	9,900e
3500 4WD LB	8.1 V8	12,000e/15,500e
3500 4WD LB	6.6 TD	12,000d/15,400d
3500 4WD LB EC	6.0 V8	9,500e
3500 4WD LB EC	8.1 V8	12,000e/15,100e
3500 4WD LB EC	6.6 TD	12,000d/15,000d
3500 4WD LB CC	6.0 V8	9,300e
3500 4WD LB CC	8.1 V8	12,000e/14,900e
3500 4WD LB CC	6.6 TD	12,000d/14,800d

Tahoe/Yukon/Suburban/Yukon XL

Vehicle	Engine	Tow Limit (lbs)
Tahoe/Yukon 1500	4.8 V8	5,700c
Tahoe/Yukon 1500	4.8 V8	6,700d
Tahoe/Yukon 1500	5.3 V8	6,700c
Tahoe/Yukon 1500	5.3 V8	7,700d
Suburban/Yukon XL 1500	5.3 V8	7,400d
Suburban/Yukon XL 1500	5.3 V8	8,400e

Vehicle	Engine	Tow Limit (lbs)
Tahoe/Yukon 1500 4WD	4.8 V8	6,400d
Tahoe/Yukon 1500 4WD	4.8 V8	7,400e
Tahoe/Yukon 1500 4WD	5.3 V8	7,400d
Tahoe/Yukon 1500 4WD	5.3 V8	8,100e
Yukon Denali 1500 AWD	6.0 V8	8,200d
Suburban/Yukon XL 1500 4WD	5.3 V8	7,300d
Suburban/Yukon XL 1500 4WD	5.3 V8	8,200e
Yukon XL Denali 1500 AWD	6.0 V8	8,000d
Suburban/Yukon XL 2500	6.0 V8	7,800d
Suburban/Yukon XL 2500	6.0 V8	9,800e
Suburban/Yukon XL 2500	8.1 V8	10,500d
Suburban/Yukon XL 2500	8.1 V8	12,000e
Suburban/Yukon XL 2500 4WD	6.0 V8	7,500d
Suburban/Yukon XL 2500 4WD	6.0 V8	9,500e
Suburban/Yukon XL 2500 4WD	8.1 V8	10,100d
Suburban/Yukon XL 2500 4WD	8.1 V8	12,000e

TD=Turodiesel; 4WD= Four Wheel Drive; EC= Extended Cab; CC= Crew Cab; LB= Long Bed. A=3.08:1 axle ratio; B=3.23:1 axle ratio; C=3.42:1 axle ratio; D=3.73:1 axle ratio; E=4.10:1 axle ratio. Note: Weight distributing hitch and sway control required over 5,000 lbs of trailer weight on light duty models, 7,500 lbs on heavy duty models.

Envoy/Trailblazer

Vehicle	Engine	Tow Limit (lbs)
2WD	4.2 I-6	5,400a,b
2WD	4.2 I-6	5,900a,c
2WD	4.2 I-6	6,400a,d
2WD LWB	4.2 I-6	5,000a,b
2WD LWB	4.2 I-6	5,500a,c
2WD LWB	4.2 I-6	6,000a,d
4WD/AWD	4.2 I-6	5,200a,b
4WD/AWD	4.2 I-6	5,700a,c
4WD/AWD	4.2 I-6	6,200a,d
4WD/AWD LWB	4.2 I-6	4,800a,b
4WD/AWD LWB	4.2 I-6	5,300a,c
4WD/AWD LWB	4.2 I-6	5,800a,d

a=weight distributing hitch and sway control required over 4,000 lb. trailer weight; b=with 3.42:1 axle ratio; c=with 3.73:1 axle ratio; d=with 4:10:1 axle ratio; LWB=Long Wheel Base

DAIMLERCHRYSLER

Chrysler/Dodge Minivans

Vehicle	Engine	Tow Limit (lbs)
Dodge Caravan	3.3, 3.8 V-6	3800i
Dodge Grand Caravan (AWD)	3.8 V-6	3,500
Town & Country	3.3, 3.8 V-6	3,800i
Town & Country (AWD)	3.8 V-6	3,500
Voyager	3.3 V-6	2000

DODGE

Vehicle	Engine	Tow Limit (lbs)
Dakota	2.5 I-4	2,200a,g
Dakota	3.9 V-6	3,700a,e*
Dakota	3.9 V-6	4,200a,f*
Dakota	3.9 V-6	5,000d,f*
Dakota	3.9 V-6	5,400d,g*
Dakota	4.7 V-8	5,650a,f*
Dakota	4.7 V-8	6,650a,g*
Dakota	4.7 V-8	5,300d,f*

Vehicle	Engine	Tow Limit (lbs)
Dakota	4.7V8	6,600d,g*
Dakota R/T	5.9V8	2,000d,g

*5,000 lb. GVWR models. 5,900 lb. GVWR models rated 100 lbs less.

Vehicle	Engine	Tow Limit (lbs)
Dakota 4WD	3.9V6	3,950a,f*
Dakota 4WD	3.9V6	4,750a,g*
Dakota 4WD	3.9V6	5,100d,g*
Dakota 4WD	4.7V8	5,400a,f*
Dakota 4WD	4.7V8	6,400a,g*
Dakota 4WD	4.7V8	5,000d,f*
Dakota 4WD	4.7V8	6,300d,g*

*5,400 lb. GVWR models. 5,900 lb. GVWR models rated 50-100 lbs less.

Vehicle	Engine	Tow Limit (lbs)
Dakota Club Cab	2.5I4	2,000a,g
Dakota Club Cab	3.9V6	3,500a,e*
Dakota Club Cab	3.9V6	4,000a,f*
Dakota Club Cab	3.9V6	4,750d,f*
Dakota Club Cab	3.9V6	5,150d,g*
Dakota Club Cab	4.7V8	5,450a,f*
Dakota Club Cab	4.7V8	6,450a,g*
Dakota Club Cab	4.7V8	5,050d,f*
Dakota Club Cab	4.7V8	6,350d,g*
Dakota R/T Club Cab	5.9V8	2,000d,g

*5,350 lb. GVWR models. 5,900 lb. GVWR models rated 50-100 lbs less.

Dakota Club Cab 4WD	3.9V6	3,750a,f*
Dakota Club Cab 4WD	3.9V6	4,550a,g*
Dakota Club Cab 4WD	3.9V6	4,900d,g*
Dakota Club Cab 4WD	4.7V8	5,150a,f
Dakota Club Cab 4WD	4.7V8	6,150a,g
Dakota Club Cab 4WD	4.7V8	4,800d,f*
Dakota Club Cab 4WD	4.7V8	6,100d,g*

*5,600 lb. GVWR models. 5,900 lb. GVWR models rated 50 lbs less.

Vehicle	Engine	Tow Limit (lbs)
Dakota Quad Cab	3.9V6	3,600a,f
Dakota Quad Cab	3.9V6	4,400a,g
Dakota Quad Cab	3.9V6	4,400d,f
Dakota Quad Cab	3.9V6	4,800d,g
Dakota Quad Cab	4.7V8	5,050a,f
Dakota Quad Cab	4.7V8	6,050a,g
Dakota Quad Cab	4.7V8	4,700d,f
Dakota Quad Cab	4.7V8	6,000d,g
Dakota Quad Cab	5.9V8	4,900d,f
Dakota Quad Cab	5.9V8	6,200d,g
Dakota Quad Cab 4WD	3.9V6	3,350a,f
Dakota Quad Cab 4WD	3.9V6	4,150a,g
Dakota Quad Cab 4WD	3.9V6	4,150d,f
Dakota Quad Cab 4WD	3.9V6	4,550d,g
Dakota Quad Cab 4WD	4.7V8	4,800a,f
Dakota Quad Cab 4WD	4.7V8	5,800a,g
Dakota Quad Cab 4WD	4.7V8	4,750d,f
Dakota Quad Cab 4WD	4.7V8	5,750d,g
Dakota Quad Cab 4WD	5.9V8	4,650d,f
Dakota Quad Cab 4WD	5.9V8	5,950d,g
Durango	4.7V8	4,650f
Durango	4.7V8	5,950g
Durango	5.9V8	5,850f

Vehicle	Engine	Tow Limit (lbs)
Durango	5.9V8	7,550g
Durango 4WD	4.7V8	4,400f
Durango 4WD	4.7V8	5,700g
Durango 4WD	5.9V8	5,600f
Durango 4WD	5.9V8	7,300g

Ram Van 1500

Vehicle	Engine	Tow Limit (lbs)
109" Wheelbase	3.9V6	4,450c,f
109" Wheelbase	5.2V8	5,450d,g
109" Wheelbase	5.2V8	5,950d,h
127" Wheelbase	3.9V6	4,250c,f
127" Wheelbase	5.2V8	6,750d,f
127" Wheelbase	5.2V8	7,750d,g
127" Wheelbase	5.9V8	7,200d,f
127" Wheelbase	5.9V8	8,200d,g
127" Wheelbase Maxi	3.9V6	4,150c,f
127" Wheelbase Maxi	5.2V8	6,650d,f
127" Wheelbase Maxi	5.2V8	7,650d,g
127" Wheelbase Maxi	5.9V8	7,100d,f
127" Wheelbase Maxi	5.9V8	8,100d,g

Ram Van 2500

Vehicle	Engine	Tow Limit (lbs)
127" Wheelbase	3.9V6	4,050c,g
127" Wheelbase	5.2V8	7,600d,f
127" Wheelbase	5.2V8	8,100d,g
127" Wheelbase	5.9V8	8,100d,g
127" Wheelbase	5.9V8	8,600d,h
127" Wheelbase Maxi	5.2V8	7,450d,g
127" Wheelbase Maxi	5.2V8	7,950d,h
127" Wheelbase Maxi	5.9V8	7,900d,g
127" Wheelbase Maxi	5.9V8	8,400d,h

Ram Van 3500

Vehicle	Engine	Tow Limit (lbs)
127" Wheelbase	5.2V8	7,550d,g
127" Wheelbase	5.2V8	8,050d,h
127" Wheelbase	5.9V8	8,050d,g
127" Wheelbase	5.9V8	8,550d,h
127" Wheelbase Maxi	5.2V8	7,400d,g
127" Wheelbase Maxi	5.2V8	7,900d,h
127" Wheelbase Maxi	5.9V8	7,900d,g
127" Wheelbase Maxi	5.9V8	8,400d,h

Ram Wagon 1500

Vehicle	Engine	Tow Limit (lbs)
109" Wheelbase	3.9V6	4,050c,f
109" Wheelbase	5.2V8	5,050d,f
109" Wheelbase	5.2V8	5,550d,g

Ram Wagon 2500

Vehicle	Engine	Tow Limit (lbs)
127" Wheelbase	5.2V8	7,200d,g
127" Wheelbase	5.2V8	7,700d,h
127" Wheelbase	5.9V8	7,650d,g
127" Wheelbase	5.9V8	8,150d,h

Ram Wagon 3500		
Vehicle	Engine	Tow Limit (lbs)
127" Wheelbase Maxi	5.2 V8	6,750d,g
127" Wheelbase Maxi	5.2 V8	7,250d,h
127" Wheelbase Maxi	5.9 V8	7,250d,g
127" Wheelbase Maxi	5.9 V8	7,750d,h

Ram Truck 1500		
Vehicle	Engine	Tow Limit (lbs)
1500	3.7 V6	3,350a,f/g
1500	3.7 V6	3,800d,f/g
1500	4.7 V8	4,800a,f
1500	4.7 V8	5,800a,g
1500	4.7 V8	4,750a,g*
1500	4.7 V8	6,750d,f
1500	4.7 V8	7,750d,g
1500	4.7 V8	6,700d,g*
1500	5.9 V8	7,650d,f
1500	5.9 V8	8,650d,g
1500	5.9 V8	7,600d,g*
1500 4WD	4.7 V8	4,550a,f
1500 4WD	4.7 V8	5,550a,g
1500 4WD	4.7 V8	4,450a,g*
1500 4WD	4.7 V8	6,450d,f
1500 4WD	4.7 V8	7,450d,g
1500 4WD	4.7 V8	6,400d,g*
1500 4WD	5.9 V8	7,400d,f
1500 4WD	5.9 V8	8,400d,g
1500 4WD	5.9 V8	7,350d,g*
1500 Quad Cab	4.7 V8	4,450a,f
1500 Quad Cab	4.7 V8	5,450a,g
1500 Quad Cab	4.7 V8	4,400a,g*
1500 Quad Cab	4.7 V8	6,400d,f
1500 Quad Cab	4.7 V8	7,400d,g
1500 Quad Cab	4.7 V8	6,350d,g*
1500 Quad Cab	5.9 V8	7,350d,f
1500 Quad Cab	5.9 V8	8,350d,g
1500 Quad Cab	5.9 V8	7,300d,g*
1500 Quad Cab 4WD	4.7 V8	4,200a,f
1500 Quad Cab 4WD	4.7 V8	5,200a,g
1500 Quad Cab 4WD	4.7 V8	4,150a,g*
1500 Quad Cab 4WD	4.7 V8	6,150d,f
1500 Quad Cab 4WD	4.7 V8	7,150d,g
1500 Quad Cab 4WD	4.7 V8	6,100d,g*
1500 Quad Cab 4WD	5.9 V8	7,100d,f
1500 Quad Cab 4WD	5.9 V8	8,100d,g
1500 Quad Cab 4WD	5.9 V8	7,000d,g*

NOTE: Short box ratings shown. Long box models are rated to tow 200 lbs less, most models. *With optional twenty-inch wheel and tire Sport Group available on short box models only.

Ram Truck 2500 Regular Cab, Longbed		
Vehicle	Engine	Tow Limit (lbs)
2500	5.9 V8	8,750a,f/h
2500	5.9 V8	8,800d,f/h
2500	8.0 V-10	13,350a,f/h
2500	8.0 V-10	13,400d,f/h
2500	5.9 TD	14,100a,f/h
2500	5.9 TD	10,150d,f
2500	5.9 TD	12,150d,h
2500	5.9 TD HO	13,950b,f/h
2500 4WD	5.9 V8	8,350a,f/h

Vehicle	Engine	Tow Limit (lbs)
2500 4WD	5.9 V8	8,400d,f/h
2500 4WD	8.0 V-10	12,950a,f/h
2500 4WD	8.0 V-10	12,950d,f/h
2500 4WD	5.9 TD	13,600a,f/h
2500 4WD	5.9 TD	9,650d,f
2500 4WD	5.9 TD	11,650d,h
2500 4WD	5.9 TD HO	13,450b,f/h

2500 Quad Cab Shortbed		
Vehicle	Engine	Tow Limit (lbs)
2500 Quad Cab	5.9 V-8	8,500a,f/h
2500 Quad Cab	5.9 V-8	8,550d,f/h
2500 Quad Cab	8.0 V-10	13,100a,f/h
2500 Quad Cab	8.0 V-10	13,150d,f/h
2500 Quad Cab	5.9 TD	13,800a,f/h
2500 Quad Cab	5.9 TD	9,900d,f
2500 Quad Cab	5.9 TD	11,900d,h
2500 Quad Cab	5.9 TD HO	13,650b,f/h
2500 Quad Cab 4WD	5.9 V-8	8,100a,f/h
2500 Quad Cab 4WD	5.9 V-8	8,100d,f/h
2500 Quad Cab 4WD	8.0 V-10	12,700a,f/h
2500 Quad Cab 4WD	8.0 V-10	12,700d,f/h
2500 Quad Cab 4WD	5.9 TD	13,400a,f/h
2500 Quad Cab 4WD	5.9 TD	9,450d,f
2500 Quad Cab 4WD	5.9 TD	11,450d,h
2500 Quad Cab 4WD	5.9 TD HO	13,250b,f/h

NOTE: Longbed models tow between 100-150 lbs less.

Ram Truck 3500 Regular Cab, Longbed		
Vehicle	Engine	Tow Limit (lbs)
3500	5.9 V-8	9,350a,f/h
3500	5.9 V-8	9,400d,f/h
3500	8.0 V-10	13,050a,f/h
3500	8.0 V-10	13,050d,f/h
3500	5.9 TD	13,750a,f/h
3500	5.9 TD	9,800d,f
3500	5.9 TD	12,800d,h
3500	5.9 TD HO	13,600b,f
3500	5.9 TD HO	15,100b,h
3500 4WD	5.9 V-8	8,900a,f/h
3500 4WD	5.9 V-8	8,950d,f/h
3500 4WD	8.0 V-10	12,600a,f/h
3500 4WD	8.0 V-10	12,650d,f/h
3500 4WD	5.9 TD	13,300a,f/h
3500 4WD	5.9 TD	9,350d,f
3500 4WD	5.9 TD	12,350d,h
3500 4WD	5.9 TD HO	13,200b,f
3500 4WD	5.9 TD HO	14,700b,h

3500 Quad Cab		
Vehicle	Engine	Tow Limit (lbs)
3500 Quad Cab	5.9 V-8	8,950a,f/h
3500 Quad Cab	5.9 V-8	9,000d,f/h
3500 Quad Cab	8.0 V-10	12,650a,f/h
3500 Quad Cab	8.0 V-10	12,650d,f/h
3500 Quad Cab	5.9 TD	13,350a,f/h
3500 Quad Cab	5.9 TD	9,400d,f
3500 Quad Cab	5.9 TD	12,400d,h

Vehicle	Engine	Tow Limit (lbs)
3500 Quad Cab	5.9 TD HO	13,200b,f
3500 Quad Cab	5.9 TD HO	14,700b,h
3500 Quad Cab 4WD	5.9 V8	8,550a,f*/h
3500 Quad Cab 4WD	5.9 V8	8,600d,f/h
3500 Quad Cab 4WD	8.0 V-10	12,200a,f/h
3500 Quad Cab 4WD	8.0 V-10	12,250d,f/h
3500 Quad Cab 4WD	5.9 TD	12,950a,f/h
3500 Quad Cab 4WD	5.9 TD	9,000d,f
3500 Quad Cab 4WD	5.9 TD	12,000d,h
3500 Quad Cab 4WD	5.9 TD HO	12,800b,f
3500 Quad Cab 4WD	5.9 TD HO	14,300b,h

*3.55:1 ratio not available in California.

NOTES: A gooseneck or fifth-wheel hitch attached to the vehicle frame should be used if the trailer being towed weighs over 10,000 lbs or has more than 1,000 lbs tongue weight. Camper Special Group Package is recommended with gooseneck or fifth-wheel applications. Use an exhaust brake for all 3500 manual transmission applications with a trailer weight over 10,000 lbs

TD= Turbo Diesel; a=five-speed manual; b=six-speed manual; c=three-speed automatic; d=four-speed automatic; e=3.21 axle; f=3.55 axle; g=3.92 axle; h=4.10 axle; i=optional Trailer Preparation Group required

FORD

Econoline Van/Wagon

Vehicle	Engine	Tow Limit (lbs) Van/Wagon
E-150	4.2 V6	5,000c/4,700c
E-150	4.6 V8	6,400c/6,100c
E-150	5.4 V8	6,800c/6,500c
E-250	4.2 V6	5,100d/NA
E-250	4.2 V6	5,500e/NA
E-250	5.4 V8	7,400d/NA
E-250 NGV	5.4 V8	6,800d/NA
E-250 Ext	4.2 V6	5,000d/NA
E-250 Ext	4.2 V6	5,400e/NA
E-250 Ext	5.4 V8	7,300d/NA
E-250 NGV Ext	5.4 V8	7,300d/NA
E-350	5.4 V8	6,300c/NA
E-350	5.4 V8	7,300e/7,300d-e
E-350 NGV	5.4 V8	6,700e/6,200e
E-350	6.8 V-10	9,200d/8,800d
E-350	6.8 V-10	10,000e
E-350	7.3 TD	9,700c/9,400c
E-350	7.3 TD	10,000e
E-350 Ext	5.4 V8	6,200c/5,700c
E-350 Ext	5.4 V8	7,200e/6,700d-e
E-350 NGV Ext	5.4 V8	6,600e/6,100e
E-350 Ext.	6.8 V-10	9,000d/8,500d
E-350 Ext.	6.8 V-10	10,000e
E-350 Ext	7.3 TD	9,600c/9,100c
E-350 Ext	7.3 TD	10,000e

Escape/Excursion/Expedition

Vehicle	Engine	Tow Limit (lbs)
Escape	3.0 V6	3,500n
Excursion	5.4 V8	6,200d
Excursion	6.8 V-10	10,100d
Excursion	6.8 V-10	10,500j
Excursion	7.3 TD	10,500d
Excursion 4WD	5.4 V8	7,200e
Excursion 4WD	6.8 V-10	9,600d
Excursion 4WD	6.8 V-10	11,000j

Vehicle	Engine	Tow Limit (lbs)
Excursion 4WD	7.3 TD	11,000d
Expedition	4.6 V8	6,300c
Expedition	5.4 V8	6,700b
Expedition	5.4 V8	7,700c,g
Expedition	5.4 V8	8,200d,g
Expedition 4WD	4.6 V8	6,000c,g
Expedition 4WD	4.6 V8	5,500c,h
Expedition 4WD	5.4 V8	6,400b
Expedition 4WD	5.4 V8	7,400c,g
Expedition 4WD	5.4 V8	6,900c,h
Expedition 4WD	5.4 V8	7,900d,g,m
Expedition 4WD	5.4 V8	7,400d,h,m

Explorer Sport (2dr) and Sport Trac, Manual/Automatic Transmission

Vehicle	Engine	Tow Limit (lbs) Manual/Auto
Explorer Sport	4.0 V6	3,060/5,120
Explorer Sport 4WD	4.0 V6	2,840/4,880
Explorer Sport Trac	4.0 V6	2,740/5,300
Explorer Sport Trac 4WD	4.0 V6	2,480/5,040

Explorer 4-Door, 5-Speed Automatic

Vehicle	Engine	Tow Limit (lbs)
Explorer	4.0 V6	3,500c
Explorer	4.0 V6	5,940d
Explorer	4.6 V8	3,500c
Explorer	4.6 V8	7,300d
Explorer 4WD	4.0 V6	3,500c
Explorer 4WD	4.0 V6	5,500d
Explorer 4WD	4.0 V6	3,500c
Explorer 4WD	4.6 V8	7,000d

Explorer 4-Door, 5-Speed Manual

Vehicle	Engine	Tow Limit (lbs)
Explorer	4.0 V6	2,700d
Explorer 4WD	4.0 V6	2,500d

F-150, Manual Transmission, Conventional Towing

Vehicle	Engine	Tow Limit (lbs)
Regular Cab	4.2 V6	2,000a
Regular Cab	4.2 V6	3,500c
Regular Cab	4.6 V8	2,000a
Regular Cab	4.6 V8	2,900b
Regular Cab	4.6 V8	3,500c
Regular Cab 4WD	4.2 V6	2,600b
Regular Cab 4WD	4.2 V6	3,200c
Regular Cab 4WD	4.6 V8	2,500b
Regular Cab 4WD	4.6 V8	3,100c
SuperCab	4.2 V6	2,000a
SuperCab	4.2 V6	3,300c
SuperCab	4.6 V8	2,000a
SuperCab	4.6 V8	2,600b
SuperCab	4.6 V8	3,200c
SuperCab 4WD	4.6 V8	2,300b
SuperCab 4WD	4.6 V8	2,900c

**F-150, Automatic Transmission,
Conventional/Fifth-Wheel Towing**

Vehicle	Engine	Tow Limit (lbs) Conv/5th-Wheel
Regular Cab	4.2 V6	4,700b/NA
Regular Cab	4.2 V6	5,700c/5,800c
Regular Cab	4.6 V8	2,000a/NA
Regular Cab	4.6 V8	6,200b/NA
Regular Cab	4.6 V8	7,200c.g
Regular Cab	5.4 V8	7,600b/NA
Regular Cab	5.4 V8	8,600c.g
Regular Cab	5.4 V8	8,800d/8,800d,o
Regular Cab NGV	5.4 V8	5,900d/NA
Regular Cab 4WD	4.2 V6	5,400c
Regular Cab 4WD	4.6 V8	5,800b/NA
Regular Cab 4WD	4.6 V8	6,800c.g/6,900c.g
Regular Cab 4WD	4.6 V8	6,300c,h/6,400c,h
Regular Cab 4WD	5.4 V8	7,200b/NA
Regular Cab 4WD	5.4 V8	7,700c,h/7,800c,h
Regular Cab 4WD	5.4 V8	8,400d/8,400d,o
SuperCab	4.2 V6	4,500b/NA
SuperCab	4.2 V6	5,500c
Super Cab	4.6 V8	2,000a/NA
Super Cab	4.6 V8	5,900b/NA
Super Cab	4.6 V8	6,900c.g
SuperCab	5.4 V8	7,300b/NA
SuperCab	5.4 V8	8,300c.g
SuperCab	5.4 V8	8,600d/8,600d,o; 8,600e,p
SuperCab 4WD	4.6 V8	5,600b/NA
SuperCab 4WD	4.6 V8	6,600c.g
SuperCab 4WD	4.6 V8	6,100c,h
SuperCab 4WD	5.4 V8	7,000b/NA
SuperCab 4WD	5.4 V8	8,000c.g
SuperCab 4WD	5.4 V8	7,500c,h
SuperCab 4WD	5.4 V8	8,200d/8,300d,o
Super Crew	4.6 V8	6,600c.g/NA*
SuperCrew	5.4 V8	8,000c.g/NA*
Super Crew 4WD	4.6 V8	6,200c.g/NA*
Super Crew 4WD	4.6 V8	6,100d,h/NA*
SuperCrew 4WD	5.4 V8	7,600c.g/NA*
SuperCrew 4WD	5.4 V8	7,100c,h/NA*

*Note: While the F-150 SuperCrew is capable of towing up to 8,000 lbs and the box will accept a fifth-wheel hitch, current fifth-wheel trailer designs are not compatible with SuperCrew. Any questions should be referred to the trailer dealer/manufacturer.

**Super Duty F-250/F-350,
Manual Transmission,
Conventional/Fifth-Wheel Towing**

Vehicle	Engine	Tow Limit (lbs) Conv/5th-Wheel
Regular Cab	5.4 V8	7,800d
Regular Cab	5.4 V8	9,300e
Regular Cab	6.8 V-10	10,700d
Regular Cab	6.8 V-10	12,500j/14,200j
Regular Cab	7.3 TD	12,500d/13,700d
Regular Cab 4WD	5.4 V8	7,400d
Regular Cab 4WD	5.4 V8	8,900e
Regular Cab 4WD	6.8 V-10	10,300d
Regular Cab 4WD	6.8 V-10	12,500j/13,800j
Regular Cab 4WD	7.3 TD	12,500d/13,300d
SuperCab	5.4 V8	7,500d
SuperCab	5.4 V8	9,000e
SuperCab	6.8 V-10	10,300d

Vehicle	Engine	Tow Limit (lbs) Conv/5th-Wheel
SuperCab	6.8 V-10	12,500j/13,800j
SuperCab	7.3 TD	12,500d/13,400d
SuperCab 4WD	5.4 V8	7,100d
SuperCab 4WD	5.4 V8	8,600e
SuperCab 4WD	6.8 V-10	9,900d
SuperCab 4WD	6.8 V-10	12,500j/13,400j
SuperCab 4WD	7.3 TD	12,500d/13,000d
Crew Cab	5.4 V8	7,200d
Crew Cab	5.4 V8	8,700e
Crew Cab	6.8 V-10	10,100d
Crew Cab	6.8 V-10	12,500j/13,600j
Crew Cab	7.3 TD	12,500d/13,100d
Crew Cab 4WD	5.4 V8	6,900d
Crew Cab 4WD	5.4 V8	8,400e
Crew Cab 4WD	6.8 V-10	9,700d
Crew Cab 4WD	6.8 V-10	12,500j/13,200j
Crew Cab 4WD	7.3 TD	12,500d/12,800d
F-350 DRW	5.4 V8	7,600d
F-350 DRW	5.4 V8	9,100e
F-350 DRW	6.8 V-10	10,300d
F-350 DRW	6.8 V-10	12,500j/13,800j
F-350 DRW	7.3 TD	12,500d-e/13,400d-e
F-350 4WD DRW	5.4 V8	7,100d
F-350 4WD DRW	5.4 V8	8,600e
F-350 4WD DRW	6.8 V-10	9,900d
F-350 4WD DRW	6.8 V-10	12,500j/13,400j
F-350 4WD DRW	7.3 TD	12,500d-e/12,900d-e
F-350 SuperCab DRW	5.4 V8	7,200d
F-350 SuperCab DRW	5.4 V8	8,700e
F-350 SuperCab DRW	6.8 V-10	10,000d
F-350 SuperCab DRW	6.8 V-10	12,500j/13,500j
F-350 SuperCab DRW	7.3 TD	12,500d-e/13,100d-e
F-350 SuperCab 4WD DRW	5.4 V8	6,900d
F-350 SuperCab 4WD DRW	5.4 V8	8,400e
F-350 SuperCab 4WD DRW	6.8 V-10	9,700d
F-350 SuperCab 4WD DRW	6.8 V-10	12,500j/13,200j
F-350 SuperCab 4WD DRW	7.3 TD	12,500d-e/12,700d-e
F-350 Crew Cab DRW	6.8 V-10	9,800d
F-350 Crew Cab DRW	6.8 V-10	12,500j/13,300j
F-350 Crew Cab DRW	7.3 TD	12,500d-e/12,800d-e
F-350 Crew Cab 4WD DRW	6.8 V-10	9,300d
F-350 Crew Cab 4WD DRW	6.8 V-10	12,500j/12,800j
F-350 Crew Cab 4WD DRW	7.3 TD	12,400d-e

**Super Duty F-250/F-350,
Automatic Transmission,
Conventional/Fifth-Wheel Towing**

Vehicle	Engine	Tow Limit (lbs) Conv/5th-Wheel
Regular Cab	5.4 V8	7,900d
Regular Cab	5.4 V8	9,400e
Regular Cab	6.8 V-10	11,200d
Regular Cab	6.8 V-10	12,500j/14,200j
Regular Cab	7.3 TD	12,500d/13,800d
Regular Cab 4WD	5.4 V8	7,500d
Regular Cab 4WD	5.4 V8	9,000e
Regular Cab 4WD	6.8 V-10	10,800d
Regular Cab 4WD	6.8 V-10	12,500j/13,800j
Regular Cab 4WD	7.3 TD	12,500d/13,400d
SuperCab	5.4 V8	7,500d

Vehicle	Engine	Tow Limit (lbs) Conv/5th-Wheel
SuperCab	5.4V8	9,000e
SuperCab	6.8V10	10,900d
SuperCab	6.8V10	12,500j/13,900j
SuperCab	7.3 TD	12,500d/13,400d
SuperCab 4WD	5.4V8	7,100d
SuperCab 4WD	5.4V8	8,600e
SuperCab 4WD	6.8V10	10,500d
SuperCab 4WD	6.8V10	12,500j/13,500j
SuperCab 4WD	7.3 TD	12,500d/13,000d
Crew Cab	5.4V8	7,300d
Crew Cab	5.4V8	8,800e
Crew Cab	6.8V10	10,600d
Crew Cab	6.8V10	12,500j/13,600j
Crew Cab	7.3 TD	12,500d/13,200d
Crew Cab 4WD	5.4V8	6,900d
Crew Cab 4WD	5.4V8	8,400e
Crew Cab 4WD	6.8V10	10,300d
Crew Cab 4WD	6.8V10	12,500j/13,300j
Crew Cab 4WD	7.3 TD	12,500d/12,800d
F-350 DRW	5.4V8	7,600d
F-350 DRW	5.4V8	9,100e
F-350 DRW	6.8V10	10,900d
F-350 DRW	6.8V10	12,500j/13,900j
F-350 DRW	7.3 TD	12,500d-e/13,400d-e
F-350 4WD DRW	5.4V8	7,200d
F-350 4WD DRW	5.4V8	8,700e
F-350 4WD DRW	6.8V10	10,500d
F-350 4WD DRW	6.8V10	12,500j/13,500j
F-350 4WD DRW	7.3 TD	12,500d-e/13,000d-e
F-350 SuperCab DRW	5.4V8	7,200d
F-350 SuperCab DRW	5.4V8	8,700e
F-350 SuperCab DRW	6.8V10	10,500d
F-350 SuperCab DRW	6.8V10	12,500j/13,500j
F-350 SuperCab DRW	7.3 TD	12,500d-e/13,100d-e
F-350 SuperCab 4WD DRW	5.4V8	6,900d
F-350 SuperCab 4WD DRW	5.4V8	8,600e/8,400e
F-350 SuperCab DRW	6.8V10	10,200d
F-350 SuperCab DRW	6.8V10	12,500j/13,200j
F-350 SuperCab 4WD DRW	7.3 TD	12,500d-e/12,800d-e
F-350 Crew Cab DRW	6.8V10	10,300d
F-350 Crew Cab DRW	6.8V10	12,500j/13,300j
F-350 Crew Cab DRW	7.3 TD	12,500d-e/12,900d-e
F-350 Crew Cab 4WD DRW	6.8V10	9,900d
F-350 Crew Cab 4WD DRW	6.8V10	12,500j/12,900j
F-350 Crew Cab 4WD DRW	7.3 TD	12,500d-e/12,400d-e

NOTE: For F-250/350 single rear wheel models, F-350 weights are shown; F-250 trailer weights may be 100-200 lbs greater. Check with your dealer for more details.

**Super Duty F-350/450/550 Chassis Cab,
Manual/Automatic Transmission,
Fifth-Wheel Towing**

Vehicle	Engine	Tow Limit (lbs) Manual/Auto
F-350	5.4V8	7,200d/7300d
F-350	5.4V8	8,700e/8,800e
F-350	6.8V10	10,100d/10,600d
F-350	7.3 TD	13,100d/13,200d
F-350 4WD	5.4V8	6,800d
F-350 4WD	5.4V8	8,300e

Vehicle	Engine	Tow Limit (lbs) Manual/Auto
F-350 4WD	6.8V10	9,700d/10,200d
F-350 4WD	7.3 TD	12,700d
F-350 DRW	5.4V8	6,900d/7,000d
F-350 DRW	5.4V8	8,400e/8,500e
F-350 DRW	6.8V10	9,700d/10,300d
F-350 DRW	6.8V10	13,200j/13,300j
F-350 DRW	7.3 TD	12,800d/e
F-350 4WD DRW	5.4V8	6,400d/6,500d
F-350 4WD DRW	5.4V8	7,900e/8,000e
F-350 4WD DRW	6.8V10	9,300d/9,800d
F-350 4WD DRW	6.8V10	12,800j
F-350 4WD DRW	7.3 TD	12,300d/e
F-350 SCC	5.4V8	6,900d
F-350 SCC	5.4V8	8,400e
F-350 SCC	6.8V10	9,700d/10,200d
F-350 SCC	7.3 TD	12,800d
F-350 4WD SCC	5.4V8	6,400d/6,500d
F-350 4WD SCC	5.4V8	7,900e/8,000e
F-350 4WD SCC	6.8V10	9,300d/9,800d
F-350 4WD SCC	7.3 TD	12,300d/12,400d
F-350 SCC DRW	6.8V10	9,400d/9,900d
F-350 SCC DRW	6.8V10	12,900j
F-350 SCC DRW	7.3 TD	12,400d/e
F-350 SCC 4WD DRW	6.8V10	9,000d/9,500d
F-350 SCC 4WD DRW	6.8V10	12,500j
F-350 SCC 4WD DRW	7.3 TD	12,000d/e
F-350 CCC	5.4V8	6,700d
F-350 CCC	5.4V8	8,200e
F-350 CCC	6.8V10	9,500d/10,000d
F-350 CCC	7.3 TD	12,600d
F-350 CCC 4WD	5.4V8	6,200d/6,300d
F-350 CCC 4WD	5.4V8	7,700e/7,800e
F-350 CCC 4WD	6.8V10	9,100d/9,600d
F-350 CCC 4WD	7.3 TD	12,100d/12,200d
F-350 CCC DRW	6.8V10	9,200d/9,700d
F-350 CCC DRW	6.8V10	12,700j
F-350 CCC DRW	7.3 TD	12,200d/e/12,300d/e
F-350 CCC 4WD DRW	6.8V10	8,700d/9,300d
F-350 CCC 4WD DRW	6.8V10	12,200j/12,300j
F-350 CCC 4WD DRW	7.3 TD	11,800d/e
F-450 DRW	6.8V10	14,500k-l/16,600k; 18,600l
F-450 DRW	7.3 TD	18,100j-k
F-450 4WD DRW	6.8V10	14,200k-l/16,300k; 18,300l
F-450 4WD DRW	7.3 TD	17,800j-k
F-450 SCC DRW	6.8V10	14,200k-l/16,200k; 18,200l
F-450 SCC DRW	7.3 TD	17,700j-k/17,800j-k
F-450 SCC 4WD DRW	6.8V10	13,800k-l/15,800k; 17,800l
F-450 SCC 4WD DRW	7.3 TD	17,300j-k/17,400j-k
F-450 CCC DRW	6.8V10	14,000k-l/16,000k; 18,000l
F-450 CCC DRW	7.3 TD	17,500j-k
F-450 CCC 4WD DRW	6.8V10	13,700k-l/15,700k; 17,700l
F-450 CCC 4WD DRW	7.3 TD	17,200j-k
F-550 DRW	6.8V10	NA/16,500k
F-550 DRW	6.8V10	NA/18,500l
F-550 DRW	7.3 TD	18,000k
F-550 4WD DRW	6.8V10	NA/16,200k
F-550 4WD DRW	6.8V10	NA/18,200l
F-550 4WD DRW	7.3 TD	17,700k
F-550 SCC DRW	6.8V10	NA/16,200k
F-550 SCC DRW	6.8V10	NA/18,200l
F-550 SCC DRW	7.3 TD	17,700k

Vehicle	Engine	Tow Limit (lbs) Manual/Auto
F-550 SCC 4WD DRW	6.8 V-10	NA/15,700k
F-550 SCC 4WD DRW	6.8 V-10	NA/17,700l
F-550 SCC 4WD DRW	7.3 TD	17,200k/17,300k
F-550 CCC DRW	6.8 V-10	NA/15,900k
F-550 CCC DRW	6.8 V-10	NA/17,900l
F-550 CCC DRW	7.3 TD	17,400k/17,500k; 21,500k,f
F-550 CCC 4WD DRW	6.8 V-10	NA/15,600k
F-550 CCC 4WD DRW	6.8 V-10	NA/17,600l
F-550 CCC 4WD DRW	7.3 TD	17,100k

NOTE: F-450/550 weights shown are for 141-inch wheelbase Regular Cab or 176-inch wheelbase Crew Cab models. For 165, 189, 200 and 201-inch wheelbase models, weights may be somewhat less (usually not more than 400 lbs). Check with your dealer for more details.

Super Duty F-650/750, All Models/Powertrains

Model	Max GVWR	Max GCWR
F-650, All Models	26,000lbs	40,000lbs GCWR*
F-750 All Models	30,000lbs	45,000lbs GCWR*
F-750 All Models	33,000lbs	60,000lbs GCWR*

*To determine maximum trailer weight, subtract your vehicle's GVWR from the maximum GCWR.

Ranger, Manual Transmission

Vehicle	Engine	Tow Limit (lbs)
Ranger	3.0 V-6	2,640d
Ranger	3.0 V-6	2,540d*
Ranger	4.0 V-6	3,560c
Ranger	4.0 V-6	3,460c*
Ranger 4WD	3.0 V-6	2,360d/e
Ranger 4WD	4.0 V-6	3,300d/e
Ranger SuperCab	3.0 V-6	2,480d
Ranger SuperCab	3.0 V-6	2,320d*
Ranger SuperCab	4.0 V-6	3,400c
Ranger SuperCab	4.0 V-6	3,260c*
Ranger SuperCab 4WD	3.0 V-6	2,200d/e
Ranger SuperCab 4WD	4.0 V-6	3,140d/e***

Ranger, Automatic Transmission

Vehicle	Engine	Tow Limit (lbs)
Ranger	2.3 I-4	2,240e
Ranger	3.0 V-6	4,100d
Ranger	3.0 V-6	4,000d*
Ranger	4.0 V-6	6,020c
Ranger	4.0 V-6	5,940c*
Ranger 4WD	3.0 V-6	3,820d/e
Ranger 4WD	4.0 V-6	5,760d/e
Ranger SuperCab	3.0 V-6	3,940d
Ranger SuperCab	3.0 V-6	3,780d*
Ranger SuperCab	4.0 V-6	5,860c
Ranger SuperCab	4.0 V-6	5,720c*
Ranger SuperCab 4WD	3.0 V-6	3,680d/e
Ranger SuperCab 4WD	4.0 V-6	5,600d/e**

*Ranger Edge only; **5,200 lbs with FX4; ***2,740 lbs with FX4.

Windstar

Vehicle	Engine	Tow Limit (lbs)
Windstar Van	3.8 V-6	2,000
Windstar Wagon	3.8 V-6	2,000

Vehicle	Engine	Tow Limit (lbs)
Windstar Wagon	3.8 V-6	3,500f

TD = Turbodiesel; Ext=Extended Cab; NGV=Natural Gas Vehicle; DRW=Dual Rear Wheels; SCC=Super Chassis Cab; CCC=Crew Chassis Cab; a= 3.08:1 axle ratio; b= 3.31:1 axle ratio; c= 3.55:1 axle ratio; d= 3.73:1 axle ratio; e= 4.09/4.10:1 axle ratio; f= Must be equipped with heavy-duty towing package; g=With 16 or 17-inch tires; h=With 17-inch tires; i= 3.27:1 axle ratio; j= 4.30:1 axle ratio; k= 4.88:1 axle ratio; l= 5.38:1 axle ratio; m=Available in high-altitude areas only; n=With Class II trailer towing package. Rating is 2,000 without; o=Available with 7700 Payload Group A only; p=Available with 7700 Payload Group B only.

HONDA

Vehicle	Engine	Tow Limit (lbs)
Odyssey	3.5 V-6	3,500a,b
Passport	3.2 V-6	4,500c

a=With transmission fluid and power steering fluid coolers and two occupants. Deduct 150 pounds per passenger up to seven passengers.; b=Without transmission fluid/power steering fluid coolers; 2,000 pounds maximum with two occupants.; c=requires load-leveling hitch.

HYUNDAI

Vehicle	Engine	Tow Limit (lbs)
Santa Fe 2WD	2.7 V-6	2,700a
Santa Fe 4WD	2.7 V-6	2,200a

a=Trailer must be equipped with brakes

ISUZU

Vehicle	Engine	Tow Limit (lbs)
Rodeo/Rodeo Sport	2.2/2.6 I-4	2,500
Rodeo Sport	3.2 V-6	4,500a
Rodeo	3.2 V-6	4,500a
Trooper	3.5 V-6	5,000a
Axiom	3.5 V-6	4,500a

a= trailer brakes required on any trailer above 3500 lbs

JEEP

Vehicle	Engine	Tow Limit (lbs)
Grand Cherokee	4.0 I-6	5,000b
Grand Cherokee	4.7 V-8	6,500b
Liberty	2.4 I-4	2,000
Liberty	3.7 V-6	5,000b,c
Wrangler	2.5 I-4	2,000a
Wrangler	4.0 I-6	2,000

NOTE: Trailer brakes required on all trailers weighing more than

1,000 pounds; a=Wrangler rating is 1,000 pounds with automatic transmission; b=Requires trailer towing package; c=Manual transmission version tows 1,500 lbs less.

KIA

Vehicle	Engine	Tow Limit (lbs)
Sportage All Models	2.0 I-4	2,000
Sedona	3.5 V-6	3,500

LAND ROVER

Vehicle	Engine	Tow Limit (lbs)
Discovery, Series II	All	5,500a,b*
Range Rover	All	6,500a,b*
Freelander	2.5 V-6	2,500a

a=Maximum trailer weight without brakes is 1,650 pounds; b=Off-road maximum is 2,200 pounds; *Can tow up to 7,700 lbs in low range

LEXUS

Vehicle	Engine	Tow Limit (lbs)
LX 470	4.7 V-8	6,500
RX 300	3.0 V-6	3,500

LINCOLN

Vehicle	Engine	Tow Limit (lbs)
Blackwood	5.4 V-8	8,700a,b
Navigator	5.4 V-8	8,800a,b

a=Requires optional Class III/IV Trailer Tow Package with load-equalizing hitch; b=4WD tow rating is 8,000 pounds.

MAZDA

Vehicle	Engine	Tow Limit (lbs)
B2500	2.5 I-4	2,240a,e
B3000	3.0 V-6	4,000a,d,e
B3000 4WD	3.0 V-6	4,360a,d,e
B4000	4.0 V-6	5,900a,c,d,e
B4000 4WD	4.0 V-6	5,700a,c,d
MPV	***	***
Tribute	3.0 V-6	3,500b

a=Requires automatic transmission; rating lower with manual transmission; b=Requires trailer-towing package; c=Requires special axle ratio and trailer-towing package; d=Requires load-equalizing hitch for more than 2,000 pounds; e=Cab Plus rating lower; ***No information available on this model at press time.

MERCEDES-BENZ

Vehicle	Engine	Tow Limit (lbs)
G-500	5.0 V-8	7,000*
ML 320	3.2 V-6	5,000
ML 430	4.3 V-8	5,000
ML55 AMG	5.5 V-8	5,000

*Late availability.

MERCURY

Vehicle	Engine	Tow Limit (lbs)
Mountaineer 4X2	4.0 V-6	5,700b
Mountaineer 4X4	4.0 V-6	5,460b,c
Mountaineer 4X2	4.6 V-8	7,300b
Mountaineer AWD	4.6 V-8	7,060b,c
Villager	3.3 V-6	2,000a
Villager	3.3 V-6	3,500b

a=Class 1 load-carrying type/weight-equalizing hitch; b=Requires optional class II towing package; c=Requires Class IV load-equalizing hitch option and 3.73 gear ratio (standard on V8)

MINI

Vehicle	Engine	Tow Limit (lbs)
Montero Limited, XLS	3.5 V-6	5,000a
Montero Sport ES, LS	3.0 V-6	5,000a
Montero Sport XLS, Limited	3.5 V-6	5,000a

a=Tow rating with trailer brakes; 1,500 pounds maximum rating without.

NISSAN

Vehicle	Engine	Tow Limit (lbs)
Pathfinder/Infinity QX4	3.5 V-6	5,000a/5,000

Vehicle	Engine	Tow Limit (lbs)
Frontier	2.4 I-4	3,500b,c
Frontier	3.3 V-6	5,000a
Frontier	3.3 V-6 SC	5,000a
Xterra	2.4 I-4	3,500
Xterra	3.3 V-6	5,000a
Xterra	3.3 V-6 SC	5,000a
Quest	3.3 V-6	3,500

a=Rating is 3,500 pounds with manual transmission; =Requires manual transmission; c=Rating is 2,000 lbs with an automatic transmission; SC=Super Charged

OLDSMOBILE

Vehicle	Engine	Tow Limit (lbs)
Bravada 2WD	4.2 I-6	5,800a,b
Bravada 2WD	4.2 I-6	6,300a,c
Bravada 4WD/AWD	4.2 I-6	5,600a,b
Bravada 4WD/AWD	4.2 I-6	6,100a,c
Silhouette	3.4 V-6	3,500d

a=weight distributing hitch and sway control required over 4,000 lb. trailer weight; b= 3.73:1 axle ratio; c= 4.10:1 axle ratio; d=requires towing package

PONTIAC

Vehicle	Engine	Tow Limit (lbs)
Aztek	3.4 V-6	3500a
Montana	3.4 V-6	3,500a

a=Requires towing package.

SATURN

Vehicle	Engine	Tow Limit (lbs)
VUE AWD	3.0 V-6	2,500 lbs

SUBARU

Vehicle	Engine	Tow Limit (lbs)
Legacy/Outback/Forester	2.5 SOHC I-4	2,000a

a=Trailer brakes required. Maximum hitch weight 200 pounds.

TOYOTA

Vehicle	Engine	Tow Limit (lbs)
4Runner	3.4 V-6	5,000
Land Cruiser	4.7 V-8	6,500
Sienna	3.0 V-6	3,500*
Tacoma	All I-4	3,500
Tacoma	3.4 V-6	5,000*
S-Runner	3.4 V-6	3,500
Sequoia	4.7 V-8	6,500
Sequoia 4WD	4.7 V-8	6,200
Highlander	All I-4	3,000*
Highlander	3.0 V-6	3,500*
Tundra 4x2 B-Cab	3.4 V-6 M	5,250
Tundra 4x2 B-Cab	3.4 V-6 A	5,200
Tundra 4x2 C-Cab	3.4 V-6 M	4,950
Tundra 4x2 C-Cab	3.4 V-6 A	4,900
Tundra 4x4 C-Cab	3.4 V-6 M	5,000
Tundra 4x4 C-Cab	3.4 V-6 A	4,950
Tundra 4x2 C-Cab (SR5, LTD)	4.7 V-8	7,200
Tundra 4x4 B-Cab	4.7 V-8	7,200
Tundra 4x4 C-Cab (SR5, LTD)	4.7 V-8	7,100

M= Manual Transmission; A= Automatic Transmission; All vehicles tongue weight is 10% of Maximum Towing Capacity; *Optional towing package required.