



## Trailer Specification Sheet

### Cross Country Model# 12HD825DO

<b>LOAD CAPACITY:</b>	21,550 Pounds
<b>TRAILER WEIGHT:</b>	6,050 Pounds
<b>G.V.W.R:</b>	27,600 Pounds
<b>MAIN FRAME:</b>	10" @ 20# per Foot Hi-Tensile Structural Channel
<b>DECK WIDTH:</b>	96" (102" Optional)
<b>DECK LENGTH:</b>	20' of Flat and 5' of Beavertail
<b>DECK FRAME:</b>	6" Channel With 4" Channel Cross Members
<b>TONGUE &amp; COUPLER:</b>	Continuation of Main Frame With Height Adjustable Pintle Eye and Chain Bin
<b>TONGUE JACK:</b>	12,000# Drop Leg, Side Wind
<b>SUSPENSION:</b>	Dual Tandem 12,000# Dexter Oil Bath Axles With Slipper Springs and Equalization
<b>TIRES:</b>	Eight ST235/80R16E Mounted on 8-Bolt Disc Wheels
<b>BRAKES:</b>	Electric, Both Axles, With Recharging Break-Away Kit
<b>DECK MATERIAL:</b>	2" Oak Plank Secured With Torx Drive Bolts
<b>TIE DOWNS:</b>	Six Forged 5/8" D-Ring, Three On Each Side of the Deck Sides
<b>RAMPS:</b>	Two, 60" Long Layover Equipment Style, Oak Filled, Adjustable With Spring Assist and Handles
<b>LIGHTS:</b>	Shock Resistant Sealed Lighting With Sealed Loom Harness
<b>ELECTRICAL PLUG:</b>	6 Prong Round or Your Choice
<b>STRIPING:</b>	Conspicuity Striping is Standard
<b>PAINT:</b>	Railplex Gray Primer With Acrylic Enamel Top Coats
<b>COLORS:</b>	Available in Any of Our Standard Colors