



## Trailer Specification Sheet

### Cross Country Model# 20HD825DO

<b>LOAD CAPACITY:</b>	35,638 Pounds
<b>TRAILER WEIGHT:</b>	6,130 Pounds
<b>G.V.W.R:</b>	41,768 Pounds
<b>MAIN FRAME:</b>	12" @ 26# per Foot Hi-Tensile Wide Flange Beam
<b>DECK WIDTH:</b>	102" Out to Out
<b>DECK LENGTH:</b>	20' of Flat and 5' of Beavertail (Beavertail Can Be Oak Filled or Self Cleaning, Your Choice)
<b>DECK HEIGHT:</b>	Approximately 34"
<b>DECK FRAME:</b>	7" Channel With 4" (5.4# per Foot) Channel Cross Members
<b>TONGUE &amp; COUPLER:</b>	Continuation of Main Frame With Height Adjustable Pintle Eye (3" ID) Adjustable From 16.75" to 32.5" and Locking Steel Toolbox
<b>TONGUE JACK:</b>	12,000# Drop Leg, Side Wind
<b>SUSPENSION:</b>	Dual Tandem 22,500# Dexter Oil Bath Axles With Slipper Springs and Equalization. Hutch 9700 Suspension
<b>TIRES:</b>	Eight LT215/75R17.5 Mounted on 10-Bolt Disc Wheels
<b>BRAKES:</b>	12-1/4" x 7-1/2" Air Brakes, With ABS On One Axle
<b>DECK MATERIAL:</b>	2" Oak Plank Secured With Torx Drive Bolts
<b>TIE DOWNS:</b>	Six Forged 1" D-Rings, Three On Each Side of the Deck Sides
<b>RAMPS:</b>	Two, 60" Long Layover Equipment Style, Oak Filled, Adjustable With Spring Assist and Handles, Your Choice of Oak Filled or Self Cleaning. Ramps Do Not Slide All the Way Together In the Center
<b>LIGHTS:</b>	Shock Resistant Sealed Lighting With Sealed Loom Harness
<b>ELECTRICAL PLUG:</b>	7 Prong Round
<b>STRIPING:</b>	Conspicuity Striping is Standard
<b>PAINT:</b>	Railplex Gray Primer With Acrylic Enamel Top Coats
<b>COLORS:</b>	Available in Any of Our Standard Colors