



## Trailer Specification Sheet Cross Country Model# 4HD16TSL

<b>LOAD CAPACITY:</b>	7,456 Pounds
<b>TRAILER WEIGHT:</b>	2,540 Pounds
<b>G.V.W.R.:</b>	9,996 Pounds
<b>OVERALL WIDTH:</b>	96"
<b>DECK HEIGHT:</b>	Approximately 16"
<b>MAIN FRAME:</b>	6" x 3-1/2" x 5/16" Structural Angle @ 9.8 Pounds per Foot
<b>CROSS MEMBERS:</b>	3" Channel @ 3.5 Pounds per Foot
<b>DECK SIZE:</b>	74" Wide by 16' Long of Flat Deck (Cross Members Are Welded Under the Sides Eliminating the Need for a Beavertail)
<b>TONGUE &amp; COUPLER</b>	6" Structural Channel, Tongue is Wrapped Back to the Front Spring Hanger, 5 Position Height Adjustable Hitch, Your Choice of Lunette Eye or 2-5/16" Ball Coupler
<b>TONGUE JACK:</b>	2,000# Flip Up, Top Wind
<b>FENDERS:</b>	Tandem Enclosed Diamond Plate
<b>SUSPENSION:</b>	Tandem 6-Bolt Drop Axles, 5 Leaf Slipper Spring Suspension and Greaseable Equalizer Bolt
<b>TIRE SIZE:</b>	ST225/75D15D Mounted On a 6-Bolt White Spoke Wheel
<b>BRAKES:</b>	12" x 2" Electric (All Wheels) With Recharging Break-Away Kit
<b>DECK MATERIAL:</b>	2" Thick Hemlock Plank Deck Secured With Torx Drive Bolts
<b>TIE DOWNS:</b>	Six D-Rings Inside Sides Three per Side, Four 4" Channel Pockets, Two per Side
<b>LOADING RAMP:</b>	One Piece With Two Sections Covered With Heavy Duty Expanded Metal, Each Ramp Section Has a Diamond Plate Approach Lip, Ramp Has Easy Lift Handles and Assist Springs
<b>LIGHTS:</b>	Shock Resistant Sealed With Loom Conduit, DOT Approved
<b>SAFETY CHAINS:</b>	5/16" Proof Coil
<b>PAINT:</b>	Railplex Gray Primer With Acrylic Enamel Top Coats
<b>COLORS:</b>	Available in Any of Our Standard Colors